



## Measurement and Modelling of the Piperazine Potassium Carbonate Solutions for CO<sub>2</sub> Capture

Fosbøl, Philip Loldrup; Thomsen, Kaj; Waseem Arshad, Muhammad

*Publication date:*  
2012

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Fosbøl, P. L., Thomsen, K., & Waseem Arshad, M. (2012). *Measurement and Modelling of the Piperazine Potassium Carbonate Solutions for CO<sub>2</sub> Capture*. Abstract from 18th Symposium on Thermophysical Properties, Boulder, CO, United States.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Measurement and Modelling of the Piperazine Potassium Carbonate Solutions for CO<sub>2</sub> Capture

Philip L. Fosbøl<sup>C</sup>, Kaj Thomsen<sup>S</sup> and M. Waseem Arshad

*The Technical University of Denmark, DTU Chemical Engineering, Kongens Lyngby, Denmark  
plf@kt.dtu.dk*

The climate is in a critical state due to the impact of pollution by CO<sub>2</sub> and similar greenhouse gasses. Action needs to be taken in order to reduce the emission of harmful components. CO<sub>2</sub> capture is one process to help the world population back on track in order to return to normal condition, obtaining a sustainable use of natural organic resources. In this work the solid solubility has been measured for the promoted hot carbonate process using piperazine and K<sub>2</sub>CO<sub>3</sub>/KHCO<sub>3</sub>. It entails a comparison of several newly developed methods in order to guarantee the accuracy of determined experimental work. Interesting and difficult phenomena has been observed in the analysis of the piperazine solvent. Various hydrates and complexes are formed. The loaded solutions are analysed using the same techniques. Guidelines for solvent handling are set up. These define a simple boundary for safe solvent handling in order to prevent precipitation during mixing. At the same time these can actively be used in the development in the process. Slurry formation is a core issue in these processes and need to be addressed carefully. The outcome of thermodynamic modelling by using the extended UNIQUAC model will be shown with the purpose of simulating the CO<sub>2</sub> capture process. This involves equilibrium studies on physical properties in the activated carbonate solvent. Energy consumption while applying the promoted carbonate solutions using piperazine is given in overview.